

DBM-ASLG-X-XK



DBM-ASLE-X-XK



| Model no | System Power | Luminous Flux | | Efficacy (lm/W) |
|-------------|--------------|---------------|-------------|-----------------|
| | | 3000K | 4000K/5000K | |
| DBM-ASLG-16 | 19W | 2138lm | 2375lm | 125 |
| DBM-ASLG-25 | 28W | 3024lm | 3360lm | 120 |
| DBM-ASLG-40 | 45W | 4658lm | 5175lm | 115 |
| DBM-ASLG-60 | 66W | 6534lm | 7260lm | 110 |

| Model no | System Power | Luminous Flux | | Efficacy (lm/W) |
|--------------|--------------|---------------|-------------|-----------------|
| | | 3000K | 4000K/5000K | |
| DBM-ASLE-40 | 43W | 4838lm | 5375lm | 125 |
| DBM-ASLE-60 | 64W | 6912lm | 7680lm | 120 |
| DBM-ASLE-80 | 84W | 8694lm | 9660lm | 115 |
| DBM-ASLE-90 | 98W | 9878lm | 10976lm | 112 |
| DBM-ASLE-120 | 118W | 11682lm | 12980lm | 110 |

Technical Parameters :

- Input Voltage : 120-277V AC
- Power Factor : >0,95
- L70 Lifespan : >60,000h
- Ambient Temperature (Ta) : -40°C ~ 50°C
- Ingress Protection : IP65
- Mechanical Impact Resistance : IK08



Features :

- cUL certified
- MEANWELL LED Driver
- 10KV surge Protection Device (SPD)
- WAGO Terminal block
- WAGO and MOLEX Quick connectors

